




ANKKASON Conduz INC.



6015 6015zz 6015 2RS Z1V1 Z2V2 Z3V3 Deep Groove Ball Bearing Distributor of SKF NSK NTN NACHI Koyo FAG OEM

Bearing No. 6015

Size	75x115x20 mm
Bore Diameter	75 mm
Outer Diameter	115 mm
Width	20 mm
d	75 mm
D	115 mm
B	20 mm
C	20 mm
r min.	1.1 mm
da min.	81 mm
Da max.	109 mm
ra max.	1.0 mm
Weight	0.645 Kg
Basic dynamic load rating (C)	39,5 kN
Basic static load rating (C0)	33,5 kN
(Grease) Lubrication Speed	5700 r/min
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	NACHI
Minimum Buy Quantity	N/A
Weight / Kilogram	0
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1 ISO P0

6015 Bearing 2D drawings and 3D CAD models



ANKKASON Conduz INC.

Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	75MM Bore; 115MM Outside Diameter; 20MM Outer Race Width; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage
Other Features	Deep Groove
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	http://www.nachiamerica.com
Inner Race Width	0 Inch 0 Millimeter
Bore	2.953 Inch 75 Millimeter
Outer Race Width	0.787 Inch 20 Millimeter
Outside Diameter	4.528 Inch 115 Millimeter
Bore Type	Cylindrical Bore
Configuration	Single Row
Bore Size	75 mm
Width	20 mm
Fillet Radius/Chamfer	1.1 mm
Dynamic Load Rating	39,500 N



ANKKASON Conduz INC.

Static Load Rating	33,500 N
Limiting Speed - Grease	5,700 rpm
Limiting Speed - Oil	6,700 rpm
Factor fo	15.7
Radial Clearance	0.010 to 0.030 mm
da (min)	81 mm
Da (max)	109 mm
ra (max)	1 mm